Air Live®
Powered by OvisLink Corp.

2012
Product Guide

www.airlive.com

Wireless 3G Router

Air3G

Air3G is a high-powered Internet sharing router with hotspot authentication, and it's compatible to both wired cable and wireless 3G network connection. Perfect for SOHO/CAFÉ/public transportation.

Air3G II

Air3G II is a wireless router with USB 3G modem port. It ensures uninterrupted internet service by switching available internet service between WAN & 3G.

Traveler 3G

Traveler 3G is a portable Internet router that allows you to share the 3G or DSL connection with friends anytime and anywhere. The rechargeable battery enhances portability and keeps you connected anytime anywhere.



Traveler 3GII

Traveler 3GII is a 3G/3.5G Wireless N Internet sharing router. The ultra compact design with rechargeable battery enhances the portability and will keep you connected anytime anywhere. It's slim, stylish and easy to carry.

Traveler 3GM

Traveler 3GM is 3G/3.5G Wireless N Internet sharing router with a built-in SIM card slot. The ultra compact design with rechargeable battery enhances the portability and can keep you connected anytime anywhere.

Wired Broadband/ADSL+ Router

ARM-204E

Featuring with 4 LAN ports and auto Internet setup wizard, ARM-204E supports ADSL2/2+ standard to provide higher performance and greater coverage from our ISP DSLAM.

Wireless Broadband Router

WN-220R

AirLive Wn-220R, 11N 150Mbps 1T1R wireless router with 4 plug &play LAN port is the center of home and office network solution.

Wireless Broadband Router

WN-350R

WN-350R is the 2nd generation of Wireless b/g/n 300Mpbs broadband router. It's ideal for sharing the Internet access via cable connection. 4-port LAN, 2R2T data stream, WDS, and multi-game mode.

WN-250R

WN-250R is the 2nd generation of Wireless b/g/n 150Mbps broadband router, which is compatible with 802.11b/g/n device and Turbo-G products. 4-port LAN, 1R1T data stream, WDS, and multi-game mode.

Wireless GIGA Router

GW-300R

GW-300R is a fascinated router with 802.11n 300Mbps wireless speed and supports 10/100/1000 Mbps 4-port LAN and 20k session fast P2P connection.

GW-300NAS

GW300NAS is a fascinated router with 802.11n 300Mbps wireless speed and supports 10/100/1000 Mbps 4-port LAN and 20k session fast P2P connection. It also equips USB port to strengthen with BT and eMule downloader.

IPv6 Router

WN-220ARM

WN-220ARM is a wireless N internet sharing router with high speed DSL connection. With IPv6 and Watchdog features, it guarantees both future proof and high performance.

Wireless ADSL2+ Router

WN-151ARM

WN-151ARM is a Wireless N Internet sharing router with high-speed DSL connection. The setup wizard offers auto DSL detection that takes only minutes to setup the network. Featuring with ADSL2/2+, WPA, Multiple SSID.

WT-2000ARM

WT-2000ARM is one of the most reliable AirLive wired & wireless routers, which supports 125Mbps Turbo-G routers, which supports 4-port LAN and auto setup wizard, you can just surf and share with ease.

Air Live®
Powered by OvisLink Corp.

Beam Forming Router

N450R

AirLive 3T3R N450R – Beam Forming Router delivers Direction sensing and Multi-path with 450Mbps 802.11 a/b/g/n concurrent dual band technology. This is ideal device for office and application has obstacles.

Wireless Repeater

N.PLUG

AirLive N.Plug is a palmed-sized portable device which combines power adapter and AP. It is designed to easy sharing and extending internet service like hotel, office, home and business traveling application. It also equips USB port for 3G dongle.

Wireless Indoor Access Point

A.DUO

The AirLive A.DUO is a concurrent dual band router in a league of its own. It features 2 wireless radios that can operate in both 5GHz and 2.4GHz at the same time. Both radios are hi-powered to provide 3 times more coverage.

N.Power

AirLive N.Power delivers up to 2 Watt maximum output power which means it can cover as much as 2.6 KM which is almost 9 times more distance than a conventional AP.

WLA-5200AP

WLA-5200AP is a 802.11a/b/g multi-functional wireless access point, and its service extender can be used as 6 wireless operation modes.

G.DUO

G.DUO can work as a router and a PoE access point with 2 wireless g/b radios in one unit. It's ideal for WISP networking solution as a 2-way CPE to reduce the deployment cost, with multiple operation modes for different application environments.

Wireless Indoor Access Point

AP60

AP60 is a 802.11b/g/n high-power multi-function access point/ router which operates in 2.4 GHz. AP60 equips with 12V(up to 24V) passive POE port. AP60 also comes with vitrual AP funtion to provide multiple SSID.

WL-5450AP

WL-5450 AP is a 802.11g multi-function wireless access point, which has 26dBm** output power(South America) and R-SMA antenna, 8 operation modes.

WL-5460AP

Reliable 802.11g multi-function wireless access point, WL-5460AP supports up to 8 operation modes, including AP, Client, Bridge, WDS, Universal Repeater, WISP and Gateway.

WL-5470AP

WL-5470AP is a 802.11g high-power multifunction access point/router, which includes a 2dBi detachable dipole antenna with R-SMA connector, 8 operation modes, and supports up to 27dBm** output power(South America) and -96dBm RSSI.

WL-5470POE

WL-5470POE is a 802.11g high-power access point, which includes 8 operation modes, 802.3af PoE, 26dBm** output power, and Telnet Managements(SSH2, HTTP, HTTPS).

N.MINI

N.MINI is a palm-size wireless enabler for the home electronic appliances. Moreover, it's a MIMO Wireless-N AP/Router/Convertor and operates at 300Mbps data transmission rate.

** For Europe Version: Max Output Power is 20dBm. For more info, please visit: www.airlive.com

Air Live®
Powered by OvisLink Corp.

Wireless Indoor Access Point

N.TOP

The N.TOP Wireless LAN POE Access Point is a MIMO indoor 802.11n 300 Mbps access point that is simple to deploy, easy to manage, and supports WDS repeater mode. It also equips WPS hardware botton for easy installation.

Wireless Outdoor CPE/Access Point

AirMax DUO

The dual-radio and dual-band 108Mbps outdoor access point with 28dBm** output Power and AirLive 14-mode firmware, AirMax DUO is suitable for all the dual band mode and perfect for solutions such as wireless hotspot network.



WHA-5500CPE

WHA-5500CPE is a 802.11a 108Mbps super range outdoor CPE with built-in 18dBi antenna, which can reach the distance of up to 25 KM. It also supports multiple operation modes, super channels, VLAN & Qos, and 802.3af Power over Ethernet.

WHA-5500CPE-NT

WHA-5500CPE-NT is a 802.11a/b/g 108Mbps super range outdoor access point with 23dBi antenna, which can reach the distance of up to 25KM. It also supports multiple operation modes, super channels, VLAN & Qos, and 802.3af Power over Ethernet.

AirMax5N

AirMax5N is a 5GHz 802.11a/n 150Mbps wireless outdoor CPE featuring with built-in directional 16dBi antenna, weather-proof housing, advanced passive PoE, up to 25dBm output power. It also supports wireless access control, client isolation. It also has R-SMA Connector for External Antenna.

AirMax5N-ESD

AirMax5N-ESD is a 5GHz 802.11a/n 150Mbps wireless outdoor CPE featuring with ethernet port lighting protection, built-in directional 16dBi antenna, weather-proof housing, advanced passive PoE, up to 25dBm output power. It also supports wireless access control, client isolation. It also has R-SMA Connector for External Antenna.

** For Europe Version: Max Output Power is 20dBm. For more info, please visit: www.airlive.com

Wireless Outdoor CPE/Access Point

AirMax2

AirMax2 is a 802.11g high-powered outdoor CPE with built-in directional 10dBi antenna and weather-proof housing. It is able to perform 9 wireless operation modes, airlogic system architecture, and bandwidth management.

WH-5420CPE

The 802.11g high-powered wireless outdoor CPE, WH-5420CPE has built-in 14dBi patch antenna, 8 operations modes, 40dBm** output power, Management (SSH, SSH2, Telnet, HTTP, HTTPS), Wireless Client Isolation.

Wireless Adapter

X.USB/X.USB-3

Palm-size 802.11 a/b/g/n dual band USB adapter, X.USB can be used as an USB dongle to connect with Wi-Fi network or as an dongle to connect with Wi-Fi network or as an outdoor AP for WISP and long distance application. (X.USB-3 includes detachable antenna)

WN-301USB

WN-301USB is a 802.11b/g/n USB dongle with software AP function, which can turn a wireless client into a wireless access point. It features with USB 2.0 and up to 300Mbps transmission speed and supports Windows 7/Vista/XP.

WN-250USB

802.11b/g/n mini USB dongle with soft-AP function, WN-250USB has installed with USB 2.0 Interface, which allows you to plug & play via 150Mbps transmission speed, and it supports WPA2, Windows/Mac OSX.

WN-370USB

AirLive WN-370USB is long distance 802.11n USB dongle with 5dBi detachable antenna and supports WEP/WPA/WPA2 standard.

** For Europe Version: Max Output Power is 20dBm. For more info, please visit: www.airlive.com

Wireless Adapter

BT-302USB

Bluetooth 3.0 Mini USB dongle that can reach up to 30 meters with 3Mbps of transmission speed and support Windows, Mac OSX and A2DP Stereo.

WN-300PCI

802.11b/g/n high speed PCI card with full compatibility with Turbo-G network, wn-300PCI features with 2T2R data stream and up to 300Mbps transmission speed, and supports WEP/WPA/WPA2 encryption.

WN-200PCI

802.11b/g/n fast transfer PCI card with full compatibility with Turbo-G network, WN-200PCI carries 1T1R data stream and up to 150Mbps transmission speed, and it also supports WEP/WPA/WPA2 encryption.

WT-2000PCI

Turbo-G PCI adapter with up to 125Mbps data transmission speed, WT-2000PCI is compatible with 802.11b/g standard, and makes your PC run at up to 2X speed as a 802.11g devices. Support 802.11e WMM(Wi-Fi Multimedia).

SNMP Managed Switches

SNMP-24MGB

Gigabits L2+ SNMP Managed Switch with 16 Gigabits SFP ports + 8 Combo Gigabit TP/SFP ports, SNMP-24MGB contains managements and advanced functionalities. It is the ideal solution for Metro and SMB application.

SNMP-GSH2404L

24+4 Gigabit Lite SNMP Managed Switch contains managements and advanced functionalities. It is the ideal solution for Metro and SMB application.

Web Managed Switches

Ether-GSH2404W

24-port 10/100/1000 Base-T Web Managed Switch with 4 combo ports (includes port 21~24), Ether-GSH2404W supports 8000 MAC addresses, which is the most cost-effective Gigabit solution as an aggregation device.

Ether-FSH2422W

24+2 port mixed Gigabit Web management Switch, Either-FSH2422W is ideal for improving the unmanaged networks to the basic managed networks.

PoE Switches

POE-FSH2422G-390

24+2-Port Mixed Gigabit Ethernet Web Smart with 390 watt PoE switch which supplies full power for all ports and equips 2 x Mini-GBIC SFP Combo Ports. It supports web management, tag VLAN, Mac Binding, Bandwidth Control and Port Trunking.

POE-FSH2422G-250

24+2-Port Mixed Gigabit Ethernet Web Smart PoE Switch equips 2 x Mini-GBIC SFP Combo Ports. It supports Bandwidth Control, Port Trunking and automaticaly detects the presence of an IEEE802.3af compliant powered device and provides up 15.4W per PoE port.

POE-FSH1608

16-port Fast Ethernet Switch with 8 port PoE, POE-FSH1608 supports up to 15.4W per each PoE port, Total Maximum is 120W.

POE-FSH804

8-port Fast Ethernet POE Switch, POE-FSH804 provides maximum 15.4W per port. Total power consumption up to 60W.

POE-FSH8PW

8-Port POE-FSH8PW is 24V DC passive POE, Web Smart Switch. It is the ideal distribution switch for AirLive's Wireless solution.

Air Live®
Powered by OvisLink Corp.

Unmanaged Switches

Ether-GSH2404

24 X 10/100/1000Mbps + 4 Mini-GBIC(Combo ports: 21~24), Ether-GSH2404 is suitable for the Enterprise, Campus, Internet Café and FTTB/FTTH Solution.

Ether-FSH2402NT

24x10/100 Mbps Fast Ethernet Port + 2 10/100/1000 Gigabit port, Ether-FSH2402NT is the best design for office network.

Ether-FSH24

Green 24-port Fast Ethernet Switch with 10.5 inch, Ether-FSH24 is designed for SMB Solution. Reduce power usage and clients' expense.

SOHO Switches



Live-8F

Green(power saving) Mini Compact 8-port Fast Ethernet Switch supports up to 1K MAC addresses and 768 bits buffer. Best choice for home and SOHO.

Live-5F

Green(power saving) Mini Compact 5-port Fast Ethernet Switch supports up to 2K MAC addresses and 384 bits buffer. Best choice for home and SOHO.



Live-8G

Mini Compact 8-port Giga Ethernet Switch with 8K MAC address, 144Kbytes buffer memory, and 9K Byte Jumbo frame. Best choice for Home and SOHO.

Live-5G

Mini Compact 5-port Giga Ethernet Switch supports up to 1K MAC addresses and 832 bits buffer. Best choice for home and SOHO.

Security Gateway & Internet Access Gateway

WIAS-3200N

WIAS-3200N is the Wireless Hotspot Gateway, which supports multiple billing & payment methods, instant account generation for up to 500 users, wireless layer-2 firewall for high security Internet service. It's ideal for Hotel, B&B, Internet Café, and Restaurant environments.

DS-100

Signal bridge between RJ-45 and RS-232

PRP-058

POS Printer

**Recommended Accessories for WIAS-3200N

Multi-Function Print Server

WFP-151U

WFP-151U is a wireless N multi-function print server that shares the services of a LAN-port connented printer to a wireless network environment, where all users who have the network access can use the printer. 150Mbps o transmission speed wirelessly.

MFP-101U

MFP-101U is a wired multi-function printer server that shares the services of a USB connected printer to a network environment. Virtual USB port/Auto release function/print server function.

Wired Print Server

P-201

1-Port parallel print server, P-201 supports both peer-to-peer and server-based printing with UPnP and installation wizard. Ideal for home and office environment.

P-201U

1-Port USB 2.0 print server, P-201U supports both peer-to-peer and server-based printing with UPnP and installation wizard. Ideal for home and office environment.

PoE Accessories

POE-100AF

Complete PoE Kits for
Your Network Devices

POE-48PB

48V PoE Power Adapter
with DC Injector

POE-48TU

802.3af PoE Splitter with
Switchable Output



POE-1P

Passive PoE Injector

POE-2P

Passive PoE Kit

Wired IPCam Surveillance VGA

POE-100CAMv2

High-performance indoor PoE IP camera, POE-100CAM provides outstanding 2-way audio to enhance the indoor surveillence environment, including communication, monitoring and rescue methods.

POE-200CAMv2

High-performance indoor Dome PoE IP camera, POE-200CAMv2 provides outstanding 2-way audio to enrich the indoor surveillance environment, including communication, monitoring and rescue methods.

Wired IPCam Surveillance VGA

IP-150CAM

IP-150CAM is an advanced VGA IP camera with 30FPS. It supports 10/100Mbps and 3/3.5G mobile phone live viewing

POE-260CAM

POE-260CAM is a PoE IP camera, featuring with Pan-Tilt, night vision, motorized movement and HTTPS encryption to enhance the Internet security. And 2-way audio can enrich the indoor surveillance environment.

Wired IPCam Surveillance 1.3MP

POE-100HD/POE-100HD-ICR

POE-100HD/POE-100HD-ICR is the H.264 PoE IP camera featuring with 1.3 Megapixel CMOS lens and auto Iris. It supports 2-way audio, mobile viewing.(POE-100HD-ICR equips IR-CUT Removable (ICR) for adapting the low-light environment)

POE-200HD

Featuring with multiple H.264, motion JPEG and MPEG-4 video streams, POE-200HD is a dome size PoE IP camera. It supports, 2-way audio, 2.5/3G/3.5G mobile phone live viewing. It's ideal for the environments, such as offices, hallways, elevators and shopping malls.

POE-250HD

Featuring with vandal resistant, POE-250HD IP camera works perfectly for both indoor environments, where are highly sensitive, such as banks, airports, casinos and ATMs, and outdoor open space, such like seaports and cargo loading areas.

OD-325HD

OD-325HD is the professional outdoor IP camera with the IR night vision function to reach up to 25m. It is designed for outdoor, featuring with IP66 weatherproof housing, includes roof casting, robust design, soak-resistant. Ideal for parking lots, warehouses, and streets monitoring.

POE-280HD

Onvif

The POE-280HD is a 1.3 Megapixel Dome type IP camera with IR LED and ICR so it provides clearly recording in both day and night time. It supports H.264 video streaming. POE-280HD can be easily installed and integrated into application such as office, hallway and elevator.

Wired IPCam Surveillance 2.0MP

IP-200PHD-24/IP-200PHD-24B

IP-200PHD-24 is H.264 Passive PoE IP Camera featuring with 2.0 Megapixel CMOS lens. It supports 2 way-audio, 2.5/3/3.5G mobile phone live viewing. It is ideal device for monitoring the indoor environment remotely. (IP-200PHD-24 has built-in SD-Slot)

POE-2600HD

POE-2600HD is the world smallest 802.3af PoE H.264 2.0 Megapixel PTZ IP camera with full HD video stream recording at 30fps, IR 15M, 2.5/3G mobile live viewing, Micro SD card and 2 ways audio. It's ideal for parking lots, warehouse, seaport and airport.

OD-2025HD/OD-2025PHD

OD-2025HD/ OD-2025PHD(802.3af/ 12v passive PoE) is a 2 Megapixel outdoor 30 fps IR IP camera. Light weight aluminum enclosure with 25M IR.

OD-2050HD

OD-2050HD is the high-end 2.0 Megapixel network camera with IP66 rated vandal proof housing and equips a 3-9mm varifocal lens for wide angle and telescopic view. Build-in IR LED provides additional light source for darker environment. The video quality is up to 1080P @ 30FPS.

OD-2060HD

Featureing with vandal resistant, OD-2060HD(PTZ, ICR, 4mm, 802.3af) IP camera works perfectly for indoors applications like banks, airports casinos and outdoor applications like seaports and cargo loading areas.

Wired IPCam Surveillance 5.0 MP

POE-5010HD

POE-5010HD is a H.264 PoE IP camera featuring with 5.0 megapixel CMOS lens with auto IRIS and IR-Cut removable. It supports IPv6, 2-way audio, 2.5/3/3.5G mobile phone live viewing. POE-5010HD is best suited for big and detailed imaging such as airport lobby and shopping mall. (Lens are available as optional accessory)

IP Camera Lens

IP Camera Lens

ACC-MPL-4mm: 4mm, Mega-Pixel CS mount Lens.

ACC-MPL-2812VF: Varifocal, 2.8~12mm, Auto-Iris (DC), Mega-Pixel CS mount Lens.

ACC-MPL-550VF: Varifocal, 5~50mm, Auto-Iris (DC), Mega-Pixel CS mount Lens.

Wireless IPCam Surveillance VGA

WN-150CAM

WN-150CAM is an advanced VGA IP camera with 30fps. It supports 802.11b/g/n, 150Mbps and 2.5/3G mobile phone live viewing.



WL-2000CAM

WL-2000CAM is a wireless IP camera, featuring with auto light sensor, UPnP, 6 high illumination LEDs, HTTPs encryption and 2-way audio. It also supports live viewing from 2.5/3/3.5G mobile phone to enhance the mobility of surveillance.

WL-2600CAM

Wireless Pan-Tilt night vision IP camera, WL-2600CAM supports night mode recording, live viewing from 2.5/3/3.5G mobile phone, 802.11g wireless data transfer. Other features include IR LEDs, UPnP, dual motion streaming.

Wireless IPCam Surveillance 1.3MP

WL-350HD

H.264,wireless IP camera, WL-350HD features with auto light sensor, 1.3MegaPixel progressive scan CMOS, and supports 2-way audio, versatile application, Windows Live messenger, live veiwing from mobile phone. The ultra-compact design makes it ideal for home environment.

Wireless IPCam Surveillance 2.0MP

WN-200HD

ONVIF

WN-200HD is a H.264 wireless IP camera featuring with 2.0 Megapixel CMOS lens. It supports 2 way audio 2.5/3/3.5G mobile phone live viewing. It's ideal for monitoring indoor application. With special self-assembly housing, it is also suitable for outdoor condition.

Wireless IPCam Surveillance 2.0MP

WN-2600HD

WN-2600HD is the world smallest Wireless N H.264 2.0 Megapixel PTZ IP camera with full HD video streaming recording at 30fps, IR night 15M, 2.5G/3G mobile live viewing, Micro SD card, 2 ways audio and 150Mbps wireless transmission rate. 86x81x97mm

Network Video Recorder

NVR4

NVR4 is a network video recorder and a data storage that supports up to 4 IP-based with H.264 video compression and keep video clips for more than 200 hours. This is the clips for more than 200 hours. This is the most cost-effective solution for protecting your home and property.

NVR8/NVR16

NVR8 supports up to 8 IP-based cameras/ NVR16 supports up to 16 IP-based cameras. They both operate without PC and equiped with GIGA LAN port, SATAII, and H.264 compression format to let the recording be fast transferred and well stored. E-map makes it easier to locate cameras.

NAS-235

NAS235 is a network attached storage provides low cost Gigabits storage space, easier management, and solid data transfer performance for multiple client connections.

Multimedia

AirVideo-2000

802.11g wireless video presenter, AirVideo-200 features with real time Audio/Video streaming to let you play back video on the projector smoothly at speed of 60fps. Ideal for conference and meeting service in hotel, or college classroom.

AirVideo-100v2

AirVideo-100v2 is 802.11 b/g/n wireless presenter dongle which is also the most efficient method to have wireless presentation. AirVideo 100v2 provides tethering feature to let PC and mobile devices have internet capability while doing the presentation.

Surveillance Software Support

AirLive CamPro Professional

AirLive CamPro Professional is 64-Channel Intelligent IP Surveillance software, which has Intelligent Video Analysis for professional video analysis. It can supports over 30 mainstream IP camera brands in the market. AirLive CamPro Professional is ideal software to manager small to large surveillance system.

CamPro Express 64

Professional network camera surveillance management software. Supports up to 64 IP cameras and 4 screen display. Drag & Play UI design enhances the IP cameras management experience.

**CamPro Express 64 is a surveillance management software that comes free with AirLive IP Cameras.

Air Live®
Powered by OvisLink Corp.

OvisLink Corp.

5F, No.96, Min-Chuan Rd., Hsin-Tien Dist., New Taipei City 231 , TAIWAN

Email: info@airlive.com

www.airlive.com